



FS Anti Foam C-2

FS Anti Foam C-2 is a concentrate defoamer used sump side to eliminate foam problems. Unlike most anti foams, the molecular structure of **AF C-2** is such that the product is extremely shear stable. Therefore, **AF C-2** can be used at lower treatment levels, and can be used less often.

NOTE: All Anti Foams should be mixed in the container prior to use for best results.

FS Anti Foam C-2 is best used in the following products:

- Synthetic Water Soluble Coolants
- Semi Synthetic Water Soluble Coolants
- Soluble Oil Coolants
- Alkaline cleaners

Treatment Levels:

- 2 ounces per 50 gallons for moderate to severe foaming applications
- 4 ounces per 50 gallons for very severe foaming applications

STORAGE/ MIXING: Anti Foam concentrates should be stored at room temperatures (between 55-90 deg. F). Should concentrates be exposed to temperatures out of this range, the concentrate needs to be mixed well prior to use. Product may become unstable/split, if exposed to extreme temperatures. Always add concentrate to water while mixing, or run concentrates through a proportioning unit.

HEALTH AND SAFETY: Refer to Safety Data Sheet for more information.

Warranty: Because conditions of use are beyond our control no representation or warranty is made in connection with the use of this product. Technical information and recommendations are believed to be accurate but are not guaranteed.

July, 2015
R: Product Tech Letterhead 2015/FS Anti Foam C-2