



FS CG 10 MS

A light Duty Multi-purpose Oil

PRODUCT APPLICATIONS

FS CG 10 MS has excellent cleanliness characteristics. The fluid is clear, very low odor and has a high flash point. This product may be used for light duty honing applications, and can be used to replace diesel fuel as a machining fluid. **FS CG 10 MS** is used straight. Do not dilute.

TYPICAL PHYSICAL PROPERTIES

Fluid Type	Straight Oil
Appearance	clear colorless
Specific Gravity	0.84
Flash Point C.O.C.	above 248 F
Weight per Gallon	7.10 lbs.
Freeze Thaw Cycle	Stable
Metal Staining	N/A, safe on ferrous and Non-ferrous metals
Viscosity @ 40°C, cSt	2

STORAGE: **FS CG 10 MS** should be stored at room temperatures (between 55 to 95 °F). Keep away from sparks, open flames, and other sources of ignition as product and empty containers could contain combustible, flammable, or ignitable substances. Do not weld or cut empty drums.

HEALTH & SAFETY: Please refer to the Safety Data Sheet (SDS) for additional information.

Warranty: Because conditions of use are beyond our control no representation or warranty is made in connection with the use of this product. Technical information and recommendations are believed to be accurate but are not guaranteed.

June, 2015

R: Product Tech Letterhead 2015/FS CG 10 MS