



# FS CG 4245

## Rust Preventative

**FS CG 4245** is an oil base, thin film preservative. Ideal for use when parts have been processed through water solutions or exposed to high humidity. It is practically odorless, and does not contain any solvents or mineral spirits, thus making the product a very low VOC product.

When using **FS CG 4245**, the product will deposit a thin, transparent, light oil film. The coating is not easily disturbed during shipping and handling and possesses residual protective characteristics even if part of the compound is wiped or rubbed from the metal surface. Due to surface-active ingredients, the coating will creep over uneven or unclean surfaces to insure a continuous film. Thus it can be used on porous metals and parts with deep crevices insuring 100% coverage.

**FS CG 4245** is to be used straight, do not cut back with solvent or water.

### TYPICAL PHYSICAL PROPERTIES

Fluid Type:	Rust Preventative
Viscosity, cSt@ 40C:	5.0-10.0
Specific Gravity:	0.84
ASTM Color:	1.0-2.5
Water Displacement:	Pass
Indoor Protection:	12+ months
Outdoor Protection:	2 weeks

**STORAGE:** **FS CG 4245** should be stored at room temperatures ( between 55 to 99°F). Keep away from sparks, open flames, and other sources of ignition as product and empty containers could contain combustible, flammable, or ignitable substances. Do not weld or cut empty drums.

**HEALTH & SAFETY:** Please refer to Safety Data Sheet (SDS) for additional information.

**Warranty:** Because conditions of use are beyond our control, no representation or warranty is made in connection with the use of this product. Technical information and recommendations are believed to be accurate but are not guaranteed.