

FS Industrial Gear Lubricant EP

ISO 68, 100, 150, 220, 320, 460, & 680

Description

FS Industrial Gear Lubricants are premium-quality oils formulated with high-viscosity-index base oils and a premium sulfur/phosphorus extreme pressure (EP) additive package. They are recommended for industrial enclosed gearing applications, including bevel, herringbone, spur and some worm gears, and wherever an AGMA extreme pressure lubricant is specified.

FS Industrial Gear Lubricants, in the proper viscosity grades, are recommended for all oil mist application systems. The same products can also be used in general plant lubrication where the performance properties of this type of lubricant are required.

Always check owner's manual for proper recommendation.

Features and Benefits:

- Exceptional EP protection and film strength
- Improved rust and corrosion protection
- Strong demulsibility for fast water separation
- Excellent oxidation and thermal stability
- Superior foam resistance
- Good seal compatibility characteristics – controls swelling, hardening, and cracking

Meets or Exceeds:

- Cincinnati Machine P-63 (ISO 68), P-77 (ISO 150), P-74 (ISO 220), P-59 (ISO 320), P-35 (ISO 460)
- US Steel 224 (ISO 68, 150, 220, 320)

Product Availability:

FS INDUSTRIAL GEAR OIL 68			
Package Size	Item Number	Package Size	Item Number
5 Gal. Pail	47475	265-gal. Totes	47477
55-gal. Drum	47476	Bulk	47478

FS INDUSTRIAL GEAR OIL 320			
Package Size	Item Number	Package Size	Item Number
5 Gal. Pail	155435	265-gal. Totes	218877
55-gal. Drum	155436	Bulk	200415

FS INDUSTRIAL GEAR OIL 100			
Package Size	Item Number	Package Size	Item Number
5 Gal. Pail	47479	265-gal. Totes	47481
55-gal. Drum	47480	Bulk	47482

FS INDUSTRIAL GEAR OIL 460			
Package Size	Item Number	Package Size	Item Number
5 Gal. Pail	155437	Bulk	188419
55-gal. Drum	155438		

FS INDUSTRIAL GEAR OIL 150			
Package Size	Item Number	Package Size	Item Number
5 Gal. Pail	47483	265-gal. Totes	47485
55-gal. Drum	47484	Bulk	47486

FS INDUSTRIAL GEAR OIL 680			
Package Size	Item Number	Package Size	Item Number
5 Gal. Pail	166014	Bulk	269543
55-gal. Drum	166015		

FS INDUSTRIAL GEAR OIL 220			
Package Size	Item Number	Package Size	Item Number
5 Gal. Pail	47487	265-gal. Totes	47489
55-gal. Drum	47488	Bulk	47490



Typical Properties:

Test / Description	Specification						
ISO Viscosity Grade	68	100	150	220	320	460	680
Viscosity @ 100°C (cSt)	8.5	11.4	14.5	18.7	24.0	30.4	44.2
Viscosity @ 40°C (cSt)	68.0	100.0	150.0	220.0	320.0	460.0	680.0
Viscosity Index	94	100	94	95	95	95	110
Density (lb/gal)	7.30	7.37	7.40	7.44	7.46	7.53	7.49
CCS Viscosity (cP)	NA	NA	NA	NA	NA	NA	NA
Pour Point (°C)	-27	-15	-15	-9	-9	-6	-6
Pour Point (°F)	-17	5	5	16	16	21	21
Flash Point (°C)	200	205	210	215	220	230	235
Flash Point (°F)	392	401	410	419	428	446	455