FS Synthetic HD Commercial ATF

Description

FS Synthetic Heavy-Duty (HD) Commercial ATF is a full synthetic lubricant formulated with a high-quality detergent and viscosity modifier additive package. This fluid is suitable for use in most heavy-duty transmission applications. FS Synthetic HD Commercial ATF is formulated with a high-quality level to support extended drain intervals, where applicable.

Features and Benefits:

- Excellent thermal and oxidative stability for long transmission life
- Exceptional all-weather performance in both hot and cold temperature extremes
- Durable friction properties to ensure smoothershifting transmissions
- Shear stable for long-term viscosity protection

Meets or Exceeds:

- Suitable for use in heavy-duty transmissions in extended drain applications*
- Allison C-4
- Man 339 Type V1, Z2
- ZF TE-ML-14B
- Voith G 607

*FS has completed extensive bench and engine tests and field-testing to support FS Synthetic HD Commercial ATF performance in a broad range of transmission applications. However, it should be noted that FS Synthetic HD Commercial ATF is not an OEM-licensed product. The respective original equipment manufacturers (OEMS) have neither endorsed nor evaluated FS Synthetic HD Commercial ATF in the respective applications listed.

Always check the owner's manual for a proper recommendation.

Product Availability:

5 Gal. Pail Item #192958 55-gal. Drum Item #226155 265-gal. Totes Item #258940 Bulk Item #258939



Typical Properties:

Test / Description	Specification
Viscosity @ 100°C (cSt)	7.4
Viscosity @ 40°C (cSt)	35.0
Viscosity Index	185
Density (lb/gal)	7.07
CCS Viscosity (cP)	NA
Pour Point (°C)	-45
Pour Point (°F)	-49
Flash Point (°C)	215
Flash Point (°F)	419